

4

3

2

1

ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED

SCALE - N.T.S.

F


F

E

E

D

D




D

Fixing							General												
IEC Frame	Pole	A	B	B1	C	H	K	AB	BB	AA	BA	BC	BA1	HA	HC	HD	L	LV	AC
280M	4&6	457	368	419	190	280	24	540	490	100	110	40	149	42	552	725	1010	115	544

C

C

T Box				Shaft					
V	q	AG	S2	D	E	F	GA	I	d5
638	360	243	2" B.S.C.	75	140	20	79.5	130	M20



Notes:-

- 1) Terminal box can be rotated in 360 deg in steps of 90 deg.
- 2) Ringed dimensions are as per IS:1231/IEC60072

B

B

Customer		Project	
P.O. No.		Consultant	
kW/Pole		Client/Contractor	
Frame		Package	
SO No.		Tag no's	

A

A

NAME	DATE	TITLE:	
DRN	YCJ	DIMENSION DRAWING	
CHD		3PH SQUIRREL CAGE, TEFC (FOOT MOUNTED) SAFE AREA INDUCTION MOTOR	
APPD			
 Bharat Bijlee AIROLI, NAVI MUMBAI		  DRG. No: A28M431TC	

4

3

2

1