

4


3

2

1



ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED

SCALE - N.T.S.

Minimum distance for efficient cooling
of motor (To be maintained by user)

IEC Frame	Pole	Fixing						General											
		A	B	B1	C	H	K	AB	BB	AA	BA	BC	BA1	HA	HC	HD	L	LV	AC
280S	2	457	368	419	190	280	24	540	490	110	110	41	149	42	552	755	1010	115	544

T Box					Shaft					
V	O	O1	q	S2	D	E	F	GA	I	d5
668	252	207	517	M50x1.5P	65	140	18	69	130	M20



Notes:-


- 1) Ringed dimensions are as per IS:1231/IEC60072
- 2) Terminal box can be rotated in 360 deg in steps of 90 deg.

Customer		Project	
P.O. No.		Consultant	
kW/Pole		Client/Contractor	
Frame		Package	
SO No.		Tag no's	

NAME	DATE	TITLE:
DRN	YCJ	07.04.2015
CHD		
APPD		

DIMENSION DRAWING

3PH SQUIRREL CAGE, TEFC (FOOT MOUNTED) FLAME PROOF(Ex'd') INDUCTION MOTOR



DRG. No:

D28S232TC

4

3

2

1